

Our Ref.: 2380-593

U.S. PATENT APPLICATION

Inventors: Brian WILLIAMS
Ina B. WIDEGREN
Johnson OYAMA

Invention: METHOD AND APPARATUS FOR ESTABLISHING A PROTOCOL
PROXY FOR A MOBILE HOST TERMINAL IN A MULTIMEDIA
SESSION

NIXON & VANDERHYE P.C.
ATTORNEYS AT LAW
1100 NORTH GLEBE ROAD
8TH FLOOR
ARLINGTON, VIRGINIA 22201-4714
(703) 816-4000
Facsimile (703) 816-4100

SPECIFICATION

METHOD AND APPARATUS FOR ESTABLISHING A PROTOCOL PROXY FOR A MOBILE HOST TERMINAL IN A MULTIMEDIA SESSION

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is related to commonly-assigned U.S. Patent
5 Application Serial No. 09/768,956, entitled "RSVP Handling in 3G Networks," filed
on January 24, 2001; U.S. Patent Application Serial No. 09/861,817, entitled
"Application Influenced Policy," filed on May 21, 2001; U.S. Patent Application
Serial No. 09/985,573, entitled "Media Binding to Coordinating Quality of Service
Requirements for Media Flows in a Multimedia Session with IP Bearer Resources,"
10 filed November 5, 2001; and U.S. Patent Application Serial No. 09/985,633, entitled
"Method and Apparatus for Coordinating Charges for Services Provided in a
Multimedia Session," filed November 5, 2001; and U.S. Patent Application Serial
No. 09/985,631, entitled "Method and Apparatus for Coordinating Quality of
Service Requirements for Media Flows in a Multimedia System With IP Bearer
Resources," filed November 5, 2001; U.S. Patent Application Serial No. 10/038,770,
entitled "Method and Apparatus for Coordinating End-to-End Quality of Service
Requirements for Media Flows in a Multimedia Session," filed January 8, 2002, and
U.S. Patent Application Serial No. 10/____,____, entitled the "A Signaling Quality of
Service Class for Use in Multimedia Communications," filed February 8, 2002, the
20 disclosures of which are incorporated herein by reference.

REFERENCE TO PRIORITY APPLICATIONS

This application claims priority from and incorporates by reference the
following commonly-assigned provisional patent applications: 60/275,354 entitled
"Enhancement of Authorization Token for RSVP Interworking," filed March 13,
25 2001.

FIELD OF THE INVENTION

The present invention generally relates to Internet Protocol (IP) networks, and more specifically, to establishing end-to-end Quality of Service (QoS) in IP networks with multimedia applications.

BACKGROUND

IP networks were originally designed to carry “best effort” traffic where the network makes a “best attempt” to deliver a user packet, but does not guarantee that a user packet will arrive at the destination. Because of the market success of IP networks, there is a clear requirement for mechanisms that allow IP networks to support various types of applications. Some of these applications have Quality of Service (QoS) requirements other than “best effort” service. Examples of such applications include various real time applications (IP Telephony, video conferencing), streaming services (audio or video), or high quality data services (browsing with bounded download delays). Recognizing these QoS requirements, the Internet Engineering Task Force (IETF), which is the main standards body for IP networking, standardized a set of protocols and mechanisms that enable IP network operators to build QoS-enabled IP networks.

Fig. 1 depicts a simplified high-level model of an IP network which may be useful in explaining QoS provisioning. As can be appreciated, the model includes two users, but could easily be expanded to include more users without changing the basic functionality of the network. In Fig. 1, User-A 101 may communicate with User-B 102 or with an application server 103. For example, in the case of an IP telephony session, User-A 101 may communicate with User-B 102. Similarly, in the case of streaming services, User-A 101 may communicate with the application server 103, which may be configured as a video server. In either case,

User-A 101 accesses an IP backbone network 104 through a local access network 105, such as PSTN (dial-in access), Global System for Mobile Communications (GSM), or Universal Mobile Telecommunications System (UMTS) network. User-B 102 is similarly connected to the IP network 104 through a local access network 106. It will be appreciated that User-A and User-B need not use the same type of access network. The IP network 104 may consist of a number of IP routers and interconnecting links that together provide connectivity between the IP network's ingress and egress points and thereby make two party communication possible. As far as the users are concerned, the perceived QoS depends on the mechanisms both in the access networks 105, 106 and on the IP backbone network 104. Of particular interest to this invention is the specific case where at least one of the access networks is a UMTS or GSM/GPRS network.

When users access IP-based services, they may use a device that runs an application program that provides the interface for the user to access the particular service. For instance, in Fig. 1, User-A may use a laptop running a conferencing application program to attend an IP network based meeting, where participants of the meeting collaborate using various programs. Such programs are well known in the art.

Various user applications may access network services through an application programming interface (API). An API provides application programmers with a uniform interface to access underlying system resources. For instance, an API may be used to configure a network resource manager to require that a particular IP packet originating from a given application receive a certain treatment from the network, such as a particular QoS. For example, if the IP network is a Differentiated Services IP network, then an application program may request that all of its IP packets receive the "Expedited Forwarding" treatment.

The User (and the API in the user's equipment) may not be aware of the different technologies that various access networks and IP backbone networks employ in order to provide QoS end-to-end, i.e., from User-A all the way to remote User-B. For instance, the application program may use an RSVP/IntServ based API, and the end-to-end embodiment in which he is involved may include a UMTS access network and a non-RSVP enabled IP network. In such cases, some "interworking" mechanisms between such different technologies and protocols are needed to make sure that the QoS is provided end-to-end.

Integrated Services (IntServ) provides a set of well-defined services which enables an application to choose among multiple, controlled levels of delivery service for its data packets. To support this capability, two things are required. First, individual network elements, such as subnets and IP routers, along the path followed by an application's data packets must support mechanisms to control the quality of service delivered to those packets. Second, a way to communicate the application's requirements to network elements along the path and to convey QoS management information between network elements and the application must be provided.

IntServ defines a number of services such as Controlled-Load (defined in IETF RFC 2211) and Guaranteed (defined in IETF RFC 2212). The service definition sets forth the required characteristics of the network equipment in order to deliver the service. The individual network elements (subnets and IP routers) that support the service must comply with the definitions defined for the service.

The service definition also defines the information that must be provided across the network in order to establish the service. This function may be provided in a number of ways, but it is frequently implemented by the resource reservation setup protocol RSVP (defined in IETF RFC 2205). RSVP (Resource reSerVation Protocol) is an IP-level resource reservation setup protocol designed for

an IntServ-enabled Internet (defined in IETF RFC 1633, 2205, and 2210). The RSVP protocol is used by a local host (e.g., User A's computer) to request a specific quality of service from the network for particular application data streams or flows along the data path between sender and receiver. RSVP is also used by routers to deliver
 5 quality-of-service requests to all nodes along the path(s) of the flows and to establish and maintain the state(s) to provide the requested service. RSVP requests generally result in resources being reserved in each node along the data path.

Fig. 2 shows an End-to-End Integrated Service between the hosts. The service is provided using routers and hosts that support the service definition defined for the required service and through signaling of the relevant information between the nodes. In order to use RSVP, each of the devices in the path between the sender and receiver must be capable of understanding and sending RSVP messages. However, some end devices may not be RSVP-enabled, and therefore, can not use RSVP to reserve bandwidth or other quality of service characteristics. An RSVP "proxy" can be defined to solve this problem by emulating an RSVP sender or receiver on behalf of such devices. More generally, a proxy is a network device, such as a router or a switch, that performs one or more functions on behalf of another device. As applied to RSVP, an RSVP Proxy originates the RSVP PATH message and receives the incoming RESV message on behalf of a non-RSVP enabled node.
 20 (PATH and RESV are examples of RSVP messages.) It also receives an incoming PATH message and originates the RESV response message on behalf of a non-RSVP enabled node. In other words, the RSVP Proxy acts on behalf of the non-RSVP enabled node to facilitate resource reservation without that node having to be involved in the RSVP signaling.

25 The problem addressed here is how to establish a protocol proxy relationship in a multimedia session involving a mobile communications access network and a non-enabled mobile terminal. A mechanism is provided that allows

the non-enabled mobile terminal to communicate a protocol proxy request with an enabled node along the send-receive path between the mobile terminal and a remote host. A mechanism is further provided to install information in the enabled node so that the node can function as the protocol proxy for the non-enabled mobile host.

5 In setting up a multimedia session between the mobile terminal and the remote host by way of an access point coupled to a packet data network, the mobile terminal sends a request message associated with the multimedia session to the access point. The message requests a packet access bearer between the mobile terminal and the access point. The mobile terminal sets an indicator in the request message to indicate that the access point should function as a communications protocol proxy for the mobile terminal for the multimedia session.

From the perspective of the access point, the received request message is asking for a packet access bearer between the mobile terminal and the access point for the multimedia session. Detecting the indicator in the request message means that the access point should function as a communications protocol proxy for the mobile terminal for the multimedia session. Accordingly, the access point performs as the communications protocol proxy for the mobile terminal for the multimedia session.

20 In one non-limiting example, the request message indicates a particular Quality of Service (QoS), and the communications protocol is the resource reservation protocol (RSVP). Thus, the access point is an RSVP proxy for the mobile terminal during the multimedia session. The mobile terminal may be a User Equipment (UE) that communicates with a General Packet Radio Service (GPRS) access network by way of a UMTS Terrestrial Radio Access Network (UTRAN). In
25 this context, the access point may be a Gateway GPRS Service Node (GGSN). The request message may be a Packet Data Protocol (PDP) context request message, and the indicator may be an RSVP proxy flag. In one example implementation, the PDP

context request message may include the RSVP proxy flag as a PDP configuration option (PCO). When the indicator is set, an RSVP proxy state process for the multimedia session is installed from a multimedia server in the GGSN. Thereafter, the RSVP proxy-GGSN generates an RSVP PATH message directed to the remote host, and in response thereto, receives an RSVP RESV message from the remote host on behalf of the mobile terminal. It also generates an RSVP RESV message in response to a received RSVP PATH message as well as generates/responds to RSVP messages other than PATH and RESV, e.g., RESVcont.

Another aspect of the invention includes a computer-generated data signal embodied in an electrical signal for use in a GPRS/UMTS network. A Packet Data Protocol (PDP) context activation, creation, modification, or update message for establishing or updating a multimedia session between a mobile terminal and a remote host includes plural fields of information. In particular, the PDP message includes a PDP configuration options (PCO) field that includes an indicator indicating whether the access point should function as a communications protocol proxy for the mobile terminal for the multimedia session. In one example implementation, the indicator field is included with an authorization token and a media binding token associated with the multimedia session.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other objects, features, and advantages of the present invention may be more readily understood with reference to the following description taken in conjunction with the accompanying drawings.

Fig. 1 is a block diagram of a high level IP network;

Fig. 2 is a block diagram depicting an example of a network employing end-to-end integrated services;

Fig. 3 illustrates a communications system in which a multimedia session may be established between a mobile terminal and a remote host;

Fig. 4 illustrates in block format various functions performed by the mobile terminal, access point, and multimedia system;

Fig. 5 is a flowchart illustrating example procedures for establishing a protocol proxy for a multimedia session in the system shown in Fig. 3;

Fig. 6 illustrates a GPRS/UMTS-based communication system for conducting multimedia sessions in which the present invention may be employed;

Fig. 7 is a block diagram illustrating a PDP context in the system shown in Fig. 6;

Fig. 8 illustrates a portion of a PDP context request message carrying an RSVP proxy flag;

Fig. 9 is a flowchart illustrating example procedures for establishing a multimedia session in the system shown in Fig. 6 where the present invention is used; and

Fig. 10 is an example signaling diagram of multimedia session message exchanges related to the procedures shown in Fig. 9.

DETAILED DESCRIPTION

In the following description, for purposes of explanation and not limitation, specific details are set forth, such as particular embodiments, procedures, techniques, etc. in order to provide a thorough understanding of the present invention. However, it will be apparent to one skilled in the art that the present invention may be practiced in other embodiments that depart from these specific

details. For example, while the present invention is described in an example application to the GSM/UMTS system, the present invention may be employed in any access network system.

In some instances, detailed descriptions of well-known methods, interfaces, devices, and signaling techniques are omitted so as not to obscure the description of the present invention with unnecessary detail. Moreover, individual function blocks are shown in some of the figures. Those skilled in the art will appreciate that the functions may be implemented using individual hardware circuits, using software functioning in conjunction with a suitably programmed digital microprocessor or general purpose computer, using an application specific integrated circuit (ASIC), and/or using one or more digital signal processors (DSPs).

In the following description, a mobile terminal is used as one example of a user equipment (UE) allowing a user access to network services. In a mobile radio communications system, the interface between the user equipment and the network is the radio interface. Thus, although the present invention is described using the term "mobile terminal," the present invention may be applied to any type or configuration of user equipment that can communicate over a radio interface.

To realize a QoS with clearly defined characteristics and functionality, a bearer must be set up from the source to the destination of the service that supports that QoS. A bearer is a logical connection between two entities through one or more interfaces, networks, gateways, etc., and usually corresponds to a data stream. A QoS bearer service includes all aspects to enable the provision of a contracted QoS. These aspects are among others the control signaling, user plane transport, and QoS management functionality. To provide IP quality of service end-to-end from mobile terminal to a remote host, it is necessary to manage the quality of service within each domain in the end-to-end path where each domain corresponds to a set of nodes utilizing the same QoS mechanisms.

As explained in the background, it may be the case that not every node in the end-to-end path supports a particular protocol being used to set up, reserve, or otherwise support a QoS related to a multimedia session. In a multimedia communication between a mobile terminal and remote host, it may be that the mobile terminal does not support a QoS reservation protocol supported by the remote host and the nodes in the end-to-end path between the mobile terminal and the remote host. In this case, the mobile terminal may request one of the nodes in the path to function as its protocol proxy to send and receive protocol messages on its behalf.

Consider the example, simplified communications system shown in Fig. 3 which permits a Mobile Terminal (MT) 10 to initiate and conduct a multimedia session with a remote host 20. In this example, the MT 10 is a non-enabled protocol host. The remote host 20 can be a fixed or wireless device, and in this example, is an enabled protocol host. The mobile terminal 10 is coupled to a radio access network (RAN) 12 over the radio interface. The RAN 12 is coupled to an Access Point 15 in a packet-switched access network (PSAN) 14. The access point 15 functions as the protocol proxy for the MT local host. Protocol messages to be sent and received by the MT 10 are sent and received by the access point 15 on behalf of the MT 10. The PSAN 14 is coupled to a Packet Data Network (PDN) 18 to which the remote host 20 is coupled. The basic traffic flow for a multimedia session (shown as solid lines) between the mobile terminal 10 and remote host 20 is transported via these three networks 12, 14, and 18. The PSAN 14 and the PDN 18 communicate multimedia control signaling (shown as dashed lines) to a Multimedia System 16 that can be separate from or an integral part of the Packet Data Network 18.

To provide further details regarding setting up a multimedia session between the MT 10 and the remote host 20, reference is now made to Fig. 4. The

mobile terminal 10 includes Access Network Bearer Control 40 coupled to multimedia session control 42. The Access Network Bearer Control block 40 transports internal bearer control signaling, which is not dedicated to a particular session, to an Access Network Bearer Control block 46 in the Access Point 15 transparently through the radio access network over a PDN signaling transport bearer. Both Access Network Bearer Control blocks 40 and 46 assist in establishing a packet access bearer for setting up the session shown as the pipe entitled “transport of session signaling.” Over this bearer, the mobile terminal 10 initiates a multimedia session including a plurality of media data streams with the remote terminal 20. Each media data stream or “flow” is transported over a corresponding packet access bearer illustrated as a “transport of media flow” pipe coupled to a Forward Media Streams block 44 in the mobile terminal. Two media flows 1 and 2 are shown for purposes of illustration in this multimedia session. The multimedia system 16 in the packet data network 18 employs a Route Media Streams block 50 to route the packets in each media flow between the mobile terminal 10 and the remote terminal/host 20. Multimedia system 16 includes a Session Control and Policy Control block 48 that utilizes session signaling from the Multimedia Session Control block 42 in the mobile terminal 10 to correlate each multimedia flow and its corresponding quality of service requirements with the session to establish necessary admission and policy enforcement rules for the session. Those rules are provided upon request to the Access Network Bearer Control block 46 which performs admission and policy enforcement operations for the session in accordance with the obtained session rules.

The protocol proxy relationship between the MT 10 and the access point 15, where the access point 15 is the proxy for the MT 10, is established during set up of each packet access bearer associated with the session. Example protocol proxy establishment procedures are described now in conjunction with the “Protocol Proxy” routine (block 60) shown in the flowchart of Fig. 5. The mobile

terminal 10 sends a request message to the access point 15 requesting a packet access bearer between the mobile terminal and the access point (block 61). The mobile terminal 10 sets an indicator in the request message to request that the access point function as a communications protocol proxy for the mobile terminal (block 62).
 5 The access point receives the request message and detects the indicator (block 63). The access point then obtains from the multimedia system information needed to function as such a proxy for one or more identified media streams in the session, e.g., from the session control and policy control 46 (block 64). Once the proxy information is installed, the access point functions as a communications protocol proxy for those media streams for the mobile terminal during the multimedia session (block 65). In particular, the access point generates/sends appropriate communications protocol messages and processes received communications protocol messages on behalf of the mobile terminal for those media streams.

Thus, even though the mobile terminal cannot directly support communications protocol messaging with the remote host, the mobile terminal can do so indirectly through the proxy. The proxy indicator, being included in the packet access bearer request message, is an easy and effective way to inform the access point of the mobile terminal's need for a communications protocol proxy. The proxy indicator is advantageously sent at the same time that various attributes of the
 15 packet access bearer are being established and configured in the access point. As
 20 these bearer attributes are being configured, the communications protocol proxy is installed in the access point.

Referring to Fig. 6, another non-limiting, example application of the invention will now be described in the context of a multimedia session set up via a
 25 General Packet Radio Service (GPRS)/Universal Mobile Telecommunication System (UMTS)-based access network 80. The packet access bearer service provided over a

GPRS/UMTS network 80 must deliver the required end-to-end bearer service including supporting a quality of service requested for that bearer.

The GPRS/UMTS network 80 includes a set of network elements between the local host, corresponding to the Mobile Terminal (MT) 88, and an external packet switching network the user is connecting to like the Internet. The radio access network (RAN) 90 provides access over the radio interface to/from the MT and includes radio base stations and radio network controllers. The RAN 90 is coupled to a GPRS packet access network 92 that includes a supporting Gateway GPRS Support Node (SGSN) 94 and a Gateway GPRS Support Node (GGSN) 96. The GGSN 96 provides interworking between the GPRS/UMTS network and the IP backbone network 84. The coupling (shown as a solid line) between the GPRS/UMTS network 80 and the IP backbone network 84 is used to transport user data IP packets.

The GPRS/UMTS-type network 80 is coupled to an IP multimedia subsystem (IMSS) 82. Communication with the IMSS 82 (shown as dashed lines) permits exchange of multimedia session control related messages. The IMSS 82 is typically a part of (although it may be separate from and coupled to) an IP backbone network 84. The remote host corresponding to user equipment (UE-B) 102 is coupled to the IP backbone network 84 through its home cellular network 86, and by signaling connection, to the IMSS 82.

The mobile terminal 88 corresponding to UE-A 88 desires to establish a multimedia session with UE-B 102. The packet traffic for this session follows the solid line couplings between the various nodes. The session is established and managed using Session Initiation Protocol (SIP), and therefore, the user equipments 88 and 102 correspond to SIP User Agents (SIP UA). The IP multimedia system 82 includes a Call State Control Function (CSCF) 98, and a Policy Control Function (PCF) 100. CSCF 98 and PCF 100 may be implemented on the same or

different servers. The Call State Control Function 98 functions as a SIP proxy for the SIP user agent UE-A 88.

Before the mobile terminal can send packet data to the remote host, the mobile terminal must “attach” to the GPRS network to make its presence known and to create a packet data protocol (PDP) context to establish a relationship with a GGSN. The PDP attach procedure is carried out between the mobile terminal and the SGSN to establish a logical link. As a result, a temporary logical link identity is assigned to the mobile terminal. A PDP context is established between the mobile terminal and a GGSN selected based on the name of the external network to be reached. One or more application flows (sometimes called “routing contexts”) may be established over a single PDP context through negotiations with the GGSN. An application flow corresponds to a stream of data packets distinguishable as being associated with a particular host application. An example application flow is in an electronic mail message from the mobile host to a fixed terminal. Another example application flow is a link to a particular Internet Service Provider (ISP) to download a graphics file from a website. Both of these application flows are associated with the same mobile host and the same PDP context. User data is transferred transparently between the MS and the external data networks with a method known as encapsulation and tunneling.

As explained earlier, QoS is a means for providing end users with satisfying service. It also enables efficient use of the radio resources. QoS can be characterized by several performance criteria such as throughput, connection setup time, percentage of successful transmissions, speed of fault detection and correction, etc. In an IP network, QoS can be measured in terms of bandwidth, packet loss, delay, and jitter. For a multimedia session between the mobile terminal and the remote host, the QoS must be end-to-end and must have the support of all nodes in the end-to-end path.

One way of ensuring such end-to-end QoS is to use the Resource Reservation Protocol (RSVP) which specifies resource reservation techniques for IP networks. RSVP is a protocol that enables resources to be reserved for a session prior to any attempt to exchange media between the MT and the remote host.

5 There are other resource reservation/assurance techniques and protocols, and the present invention can be used with these as well. However, for purposes of explanation, the following example embodiment is described in the context of RSVP.

In RSVP, a sender first issues a PATH message to the remote receiver via a number of routers. The PATH message contains a traffic specification (Tspec) that provides details about the data that the sender expects to send in terms of bandwidth requirement and packet size. Each RSVP-enabled router along the way establishes a path state that includes the previous source address of the PATH message (i.e., the next hop back towards the sender). The receiver of the PATH message responds with a Reservation Request (RESV) that includes a flowspec. The flowspec includes a Tspec and information about the type of reservation service requested. These are the primary RSVP messages handled by the RSVP proxy, but the proxy preferably handles any other RSVP messages, e.g., RSVP RESVcont, as well.

A problem with the multimedia session being established between the mobile terminal 88 and the remote host 102 in Fig. 6 is that the mobile terminal 88 is a non-enabled RSVP host. However, the rest of the IP routers in the path to the RSVP-enabled remote host 102 support RSVP. Thus, in order to use RSVP to reserve resources end-to-end for this session, the mobile terminal 88 needs an RSVP proxy. In this case, the GGSN 96 is chosen to perform that proxy role. The next

20 step is to let the GGSN 96 know that the mobile terminal 88 needs the GGSN to be the mobile's RSVP proxy for this session. This information is communicated to the

25

GGSN 96 when one or more Packet Data Protocol (PDP) contexts is being established for the session.

Within a GPRS/UMTS access network, radio network resources are managed on a per PDP context level, which corresponds to one or more user flow/data streams and a certain QoS class. A PDP context is implemented as a dynamic table of data entries, comprising all needed information for transferring PDP data units between the mobile terminal and the GGSN, e.g., addressing information, flow control variables, QoS profile, charging information, etc. The relationship between a packet access bearer and a PDP context is a one-to-one mapping. The PDP context signaling carries the requested and negotiated QoS profile between the nodes in the UMTS network. It has a central role for QoS handling in terms of admission control, negotiation, and modifying of bearers on a QoS level.

A PDP context is shown in Fig. 7. Briefly, the MT sends a PDP message, e.g., “Activate PDP context request,” to the SGSN which includes a requested QoS profile. The SGSN sends “RAB Assignment Request” to the RNC in the RAN to establish a radio access bearer (RAB) service to carry the RAB QoS attributes. From the RAB QoS attributes, the RNC determines the radio-related parameters corresponding to the QoS profile, e.g., transport format set, transport format combination set, etc. The RNC sends a “Radio Bearer Set-up” message to the MT. The RAN and the MT are ready to transfer traffic, and a “RAB Assignment Complete” message is sent to the SGSN.

The SGSN sends a “Create PDP Context Request” to the GGSN carrying the QoS profile. Based on this profile, an admission control is performed at the GGSN level, and the GGSN may restrict the QoS if, for example, the system is overloaded. The GGSN stores the PDP context in a database. The GGSN returns the negotiated QoS to the SGSN in a “Create PDP Context Response” message and

the SGSN stores the PDP context in its database. The negotiated QoS is sent from the SGSN to the MS in an "Activate PDP Context Accept" message. If either the SGSN or the GGSN has modified the QoS profile, then the MS has to either accept or reject this profile.

5 The mobile terminal 88 can indicate to the GGSN 96 its need for an RSVP proxy in PDP context request either in activating/creating a new PDP context or modifying/updating an existing one. A single bit field can be included in the PDP context request called the RSVP proxy flag or indicator. If the flag is set, the MT requests the GGSN to be its RSVP proxy. If the flag is not set, the GGSN need not be its RSVP proxy. In one non-limiting example, the RSVP proxy flag field may be incorporated as a PDP Configuration Options (PCO) parameter in the PDP context request message. Preferably, (although not necessarily), the RSVP proxy flag field is included as a PCO along with one or more "tokens" associated with the session. Fig. 8 shows a partial PCO in a partial PDP context request message. The PCO includes three example tokens: a session identifier (ID), which can be used as an authorization token, a media binding indicator (MBI), which is a token that identifies a media flow within the session, and the RSVP proxy flag field/token. Further information regarding session IDs, MBIs, and other session-related tokens may be found in several of the commonly-assigned, related applications listed above, 15 the disclosures of which are incorporated herein by reference.

20

Reference is now made to the Multimedia Session routine (block 110) in Fig. 9 which outlines in flowchart form example procedures for establishing a multimedia session between the MT (UE-A) and the remote host (UE-B). In particular, the MT (UE-A) requests that the GGSN function as its RSVP proxy using 25 the PDP context request message format show in Fig. 9. A session signaling GPRS bearer is established between UE-A and the GPRS network 92 using well-established GPRS PDP context activation messages. This session signaling GPRS bearer

corresponds to a first or primary PDP context (block 112). UE-A requests a multimedia session with the SIP UA remote UE-B over the session signaling GPRS bearer via the RAN 90, the GPRS network 92, the IP multimedia subsystem 82, the IP backbone network 84, and UE-B's home cellular network 86 (block 114). This request may be in the form of an SIP/SDP message sequence which contains sufficient information about the session, such as the source (UE-A) and destination (UE-B) end points, bandwidth requirements, and the characteristics of the media exchange, etc. to trigger an authorization of QoS resources procedure in the Call State Control Function 98.

The Policy Control Function 100 authorizes, if appropriate, the required quality of service resources for the session and installs an IP bearer level policy for the session and each media flow based on the information from the Call State Control Function 98. In addition, the Policy Control Function 100 generates an authorization "token" for the session corresponding to a session identifier. When the multimedia session is authorized and the policy control function 100 stores session information for each of the media flows in the session, the mobile terminal generates media binding information (MBI) for each media data stream in the session. The mobile terminal determines that the GGSN should function as its RSVP proxy for selected media data streams in the session (block 116).

The mobile terminal requests a PDP context for each media stream and includes the session id, the MBI, and the RSVP proxy indicator to the GGSN in the PDP context request message as a PCO. The MBI is used to retrieve session, media, and policy related information from the multimedia system. Because the RSVP proxy flag is set, information needed for the GGSN to function as the RSVP proxy is also retrieved from the multimedia system (block 118). The session, media, and policy related information is used to decide if the PDP context is allowed to be established (admission control). The retrieved proxy information configures the

GGSN as an RSVP proxy, e.g., generating RSVP PATH messages and receiving RSVP RESV messages on behalf of the mobile terminal for the session (block 120).

An example signaling flow diagram for the example multimedia session between the mobile terminal local host UE-A and remote host UE-B is shown in Fig. 10 and now described. Initially, UE-A establishes a first PDP context with the GGSN to establish a GPRS bearer for session signaling needed to establish the multimedia session. The UE-A then registers with the CSCF before sending a SIP INVITE message on the GPRS signaling bearer to the CSCF to setup the IP multimedia session. The INVITE message includes the session details regarding the number of media flows and requested corresponding quality of service. The CSCF authenticates the UE-A as a subscriber and authorizes the session. The SIP INVITE message is forwarded to UE-B via external networks. UE-B confirms the session request in a SIP “183” message returned to the CSCF. The SIP 183 is an acknowledgement message to the SIP INVITE message.

The CSCF requests from the PCF a session identifier (ID) for the session and communicates session-related and media-related data to the PCF. The session ID corresponds to an authentication token. The PCF registers the session-related data and the media-related data, makes policy decisions for the session, issues the session ID (authorization token), and returns it to the CSCF. The CSCF confirms the session, and delivers the session ID in a SIP 183 message to the UE-A.

The UE-A determines media information from each media stream, and generates media binding information (MBI) for each media stream using the session ID and the media information. Alternatively, the UE-A may receive the MBI from the CSCF in the SIP 183 message or from another entity. Still further, the UE-A may create the MBI using some other procedure that does not employ the session ID. In addition, the UE-A determines its need for an RSVP proxy. The UE-A activates a second PDP context (i.e., by sending a secondary PDP context request message to

the SGSN) for each media stream and includes in the PCO the session id, the MBI, and sets the RSVP proxy flag.

The GGSN checks the PCO and detects the session id, the MBI, and the RSVP proxy flag. The GGSN uses the MBI as an identifier for each media stream and requests the policy/rules for the session and media stream in a Common Open Policy Service Protocol (COPS) REQ message. RSVP proxy information is also requested. In response, the PCF retrieves the session information and policy decisions associated with the MBI for each media stream and returns the policy rules and other session-related and media-related information to the GGSN in a COPS DEC message. The PCF also provides RSVP proxy information to be installed in the GGSN. Using the obtained rules and information, the GGSN enforces the policy and installs the RSVP proxy information. It acknowledges the request for each secondary PDP context. The GGSN responds with a COPS RPT message.

Thereafter, the GGSN is enabled as an RSVP proxy for the UE-A, generating and terminating RSVP signaling for each media stream to/from UE-B. As an RSVP proxy, the GGSN generates an RSVP PATH message for each media data stream to UE-B, which is then confirmed by an RSVP RESV message from the UE-B. This is done for the establishment of the RSVP flow from the GGSN to the UE-B. The GGSN RSVP proxy responds to each RSVP PATH message from UE-B with an RSVP RESV message. This is done to establish the RSVP flow from the UE-B to the GGSN. Two RSVP flows are established for each bidirectional media data stream for which GGSN has established the RSVP proxy function.

While the present invention has been described with respect to particular embodiments, those skilled in the art will recognize that the present invention is not limited to these specific exemplary embodiments. Different formats, embodiments, and adaptations besides those shown and described as well as many

variations, modifications, and equivalent arrangements may also be used to implement the invention. Therefore, while the present invention has been described in relation to its preferred embodiments, it is to be understood that this disclosure is only illustrative and exemplary of the present invention. Accordingly, it is intended
5 that the invention be limited only by the scope of the claims appended hereto.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
222